



FOR D38999/24 CONNECTORS “D” SLOT KEYING

PART NUMBER	A +/- .005	B +/- .005	C +/- .005	D	SHELL SIZE	WEIGHT LBS.
10RL9-N010	0.674	1.12	0.654	0.859-0.945	9	0.005
10RL9-N011	0.792	1.24	0.751	0.984-1.063	12	0.010
10RL9-R012	0.989	1.43	0.937	1.172-1.260	13	0.015
10RL9-S005	1.107	1.59	1.060	1.296-1.417	15	0.015
10RL9-T006	1.256	1.63	1.185	1.422-1.457	17	0.015
10RL9-Z026	1.383	1.79	1.310	1.545-1.614	19	0.015
10RL9-Z027	1.501	1.89	1.447	1.672-1.811	21	0.020
10RL9-Z028	1.619	2.14	1.551	1.796-1.969	23	0.025
10RL9-Z029	1.737	2.19	1.683	1.939-2.017	25	0.025

BASE MATERIAL: STAINLESS STEEL 17-7, Rockwell Hardness Rc 43 min. Finish Options listed below.

FINISH	SUFFIX	STC SPECIFICATION	NO SUFFIX MEANS NO FINISH
ZINC	-Z	QQ-Z-325, CLASS 2, TYPE II	SUFFIX IS NOT MARKED ON PART
ELECTROLESS NICKEL	-E	MIL-C-26074, CLASS 1, GRADE A	SUFFIX MARKING ON PAPERWORK ONLY

Saint Technologies, Inc. 10 North Locust P.O. Box 66 Shannon, IL 61078 Phone: 815.864.3035 Fax: 815.864.3134 CAGE 60198	TITLE: REALLOCK™, FOR D38999/24 CONNECTORS & “D” SLOT KEYING	CHART NUMBER
		10RL9
		REV. E 08/19/2009 ECO S0063