



## FOR D38999/24 CONNECTORS “SERIES III”

PART NUMBER	A +/- .005	B +/- .015	C +/- .005	D	SHELL SIZE	WEIGHT LBS.
RL9-N010	0.674	1.12	0.654	0.859-0.945	9	0.005
RL9-N011	0.792	1.24	0.754	0.984-1.063	11	0.007
RL9-R014	0.989	1.43	0.941	1.172-1.260	13	0.010
RL9-S005	1.107	1.59	1.065	1.296-1.417	15	0.010
RL9-T006	<u>1.265</u>	1.63	1.190	1.422-1.457	17	0.010
RL9-Z026	1.383	1.79	1.314	1.545-1.614	19	0.013
RL9-Z027	1.501	1.98	1.438	1.672-1.811	21	0.011
RL9-Z028	1.621	2.14	1.567	1.796-1.969	23	0.011
RL9-Z029	1.737	2.19	1.688	1.939-2.017	25	0.012

**BASE MATERIAL: STAINLESS STEEL 17-7, Rockwell Hardness Rc 43 min. Finish Options listed below.**

FINISH	SUFFIX	STC SPECIFICATION
ZINC	-Z	QQ-Z-325, CLASS 2, TYPE II
ELECTROLESS NICKEL	-E	MIL-C-26074, CLASS 1, GRADE A

<b>Saint Technologies, Inc.</b> 10 North Locust P.O. Box 66 Shannon, IL 61078 Phone: 815.864.3035 Fax: 815.864.3134	TITLE: REALLOCK™, FOR D38999/24 CONNECTORS & “D” SLOT KEYING CAGE: 60198	CHART NUMBER 2013
		REV. D 08/29/2011 ECO S078

THIS DRAWING AND INFORMATION HEREIN IS THE EXCLUSIVE PROPERTY OF SAINT TECHNOLOGIES, INC. AND UNAUTHORIZED USE OR REPRODUCTION THEREOF IS PROHIBITED.