



MATERIAL: 6061-T6 ALUMINUM ALLOY

FINISH: OLIVE DRAB CADMIUM PLATING PER QQ-P-416 TYPE 2, CLASS 3, OVER ELECTROLESS NICKEL BASE PER ASTM B733-90. FINAL FINISH TO BE CONDUCTIVE.

NOTES:
1. MAX. RADIUS ON NUT POINTS IS 0.010 INCHES

D 38999/24 SHELL SIZE	"P" DIM. INCHES +/-0.005	"A" DIM. METRIC	STI PART NUMBER	USED WITH STI #
9	0.890	M 17 X 1-6 H	NRL-3009	RL9-N007
11	1.038	M 20 X 1-6 H	NRL-3011	RL9-N008
13	1.235	M 25 X 1-6 H	NRL-3013	RL9-R010
15	1.375	M 28 X 1-6 H	NRL-3015-01	RL9-S004
15	1.392	M 28 X 1-6 H	NRL-3015	RL9-S004
17	1.433	M 32 X 1-6 H	NRL-3017	RL9-T005
19	1.589	M 35 X 1-6 H	NRL-3019	RL9-Z022
21	1.786	M 38 X 1-6 H	NRL-3021	RL9-Z023
23	1.941	M 41 X 1-6 H	NRL-3023	RL9-Z024
25	1.990	M 44 X 1-6 H	NRL-3025	RL9-Z025

D	ECO S0028	8/19/04	JFLB	B	ECO S0013	7/29/2003	JFLB
C	ECO S0014	8/14/03	JFLB	A	ECO S0012	6/13/2003	JFLB

This drawing and information herein is the exclusive property of Saint Technologies, Inc. and unauthorized use or reproduction thereof is prohibited.

REV. LTR.	REVISION	DATE	APPROVED
-----------	----------	------	----------

Unless Otherwise Specified;
Dimensions Are In Inches
TOLERANCE ON:

One Place	(.0)	±.030
Two Places	(.00)	±.015
Three Places	(.000)	±.005
Angles		± 4°

TITLE REALLOCK™ NUTS FOR USE WITH CHART 2011		MATERIAL SEE BOX ABOVE	
MFG. CAGE CODE 60198 Shannon, IL 61078	DRAWN	JFB	5/01/03
	CHECKED	JFB	5/01/03
	APPROVED	JFB	5/01/03
			CHART N2000
			DRAWING NUMBER